




TEBAOFLEX CABLE

DATA SHEET

Mining&Industrialcable

MINE FEEDER TYPE 1 SCREENED MACHINE CABLE

1.1/1.1 kV PVC insulated and covered screened cable to AS/NZS 1972



APPLICATION

Screened cable for wiring mobile equipment such as continuous miners, shuttle cars, road headers and personnel transport systems. Used for interconnection of equipment including control boxes and motors. Further mechanical protection is required for external non-protected installations.

CONSTRUCTION

Parameter	Value
Conductor	Tinned annealed copper conductor
Insulation	Heat resistant V-90 PVC
Screen	Tinned copper wire and polyester yarn composite braid screen
Screening option	Cores can be individually or collectively screened
Cover	Heat resistant 5V-90 PVC

CABLE CHARACTERISTICS

Parameter	Value
Standard	AS/NZS 1972
Rated voltage	1.1/1.1 kV
Maximum continuous operating temperature	+90 deg C
Minimum installation temperature	0 deg C
Installation conditions	In duct machines; further mechanical protection required
Oil / water performance	Very good splash resistance and very good flexibility
Flame performance	C3

TECHNICAL DATA

Complete nominal dimensional data. Source ordering codes have been omitted.

1.1/1.1 kV TYPE 1 - INDIVIDUALLY SCREENED - ELECTRICAL DATA

Area mm ²	Cores	Cond. dia. mm	Insul. thick. mm	AC res. 90 deg C oh/km	React. 50 Hz oh/km	Volt drop mV/A.m	Max DC res. combined oh/km
1.5	2	1.6	0.8	17.5	0.120	30.3	13.7
1.5	3	1.6	0.8	17.5	0.120	30.3	13.7
10	3	4.6	1.0	2.58	0.0923	4.47	6.06
16	3	6.2	1.0	1.58	0.0854	2.74	3.72
1.5	4	1.6	0.8	17.5	0.128	30.3	13.7
10	4	4.6	1.0	2.58	0.0998	4.47	6.06
16	4	6.2	1.0	1.58	0.0929	2.74	3.72

1.1/1.1 kV TYPE 1 - INDIVIDUALLY SCREENED - DIMENSIONS AND MASS

Area mm ²	Cores	Covering thick. mm	Nom. dia. mm	Approx mass kg/100m
1.5	2	0.8	10.2	15
1.5	3	0.8	10.8	20
10	3	1.0	18.1	60
16	3	1.3	22.0	85
1.5	4	0.8	11.9	25
10	4	1.3	20.5	75
16	4	1.3	24.3	110

1.1/1.1 kV TYPE 1 - COLLECTIVELY SCREENED - ELECTRICAL DATA

Area mm ²	Cores	Cond. dia. mm	Insul. thick. mm	AC res. 90 deg C oh/km	React. 50 Hz oh/km	Volt drop mV/A.m	Max DC res. combined oh/km
1.5	2	1.6	0.8	17.5	0.106	30.3	13.7
1.5	3	1.6	0.8	17.5	0.106	30.3	13.7
1.5	4	1.6	0.8	17.5	0.114	30.3	13.7
1.5	6	1.6	0.8	17.5	0.123	30.3	13.7
1.5	16	1.6	0.8	17.5	0.152	30.3	13.7
1.5	30	1.6	0.8	17.5	0.169	30.3	13.7

1.1/1.1 kV TYPE 1 - COLLECTIVELY SCREENED - DIMENSIONS AND MASS

Area mm ²	Cores	Covering thick. mm	Nom. dia. mm	Approx mass kg/100m
1.5	2	0.8	9.38	15
1.5	3	0.8	9.88	15
1.5	4	0.8	10.7	20
1.5	6	1.0	12.8	25
1.5	16	1.3	18.8	55
1.5	30	1.5	24.7	90

Notes: Cables rated in excess of 20 amps are electrically symmetrical.

CERTIFICATIONS



TEBAOFLEX CABLE