




TEBAOFLEX CABLE

DATA SHEET

Mining&Industrial cable

SANS TYPE 622 / 622-ECC 12.7/22 KV CABLE

Medium voltage screened reeling and section feeder cable



APPLICATION

Designed for electrically driven machines, movable electric apparatus in hazardous areas, portable electric apparatus and section feeders. Suitable for open-cast mining, medium sized draglines, shovels and drills, reeling purposes and other industrial applications.

CONSTRUCTION

Parameter	Value
Conductor	Class 5 flexible stranded tinned annealed copper
Insulation	EPR thermosetting compound with strippable semi-conducting core screen, triple extruded
Braid	Nylon / tinned copper wires
Pilot cores	Insulated with EPM
Lay	Each power core individually screened with tinned copper / textile braid and laid up with three insulated pilot cores
ECC variant	One pilot core replaced with tinned conductor
Inner sheath	CR polychloroprene rubber
Reinforcement braid	Open nylon braid, minimum 16 strings
Outer sheath	CR polychloroprene rubber, black

CABLE CHARACTERISTICS

Parameter	Value
Standard	SANS 1520-2; SANS 1411-1; SANS 1411-3
Rated voltage	12.7/22 kV
Temperature rating	-25 deg C to +90 deg C
Minimum bending radius	9 x overall diameter
Performance	UV resistant, sunlight resistant and oil resistant
Sheath colour	Black

TECHNICAL DATA

Complete nominal dimensional data. Source ordering codes have been omitted.

TYPE 622 DIMENSIONS									
Cond. size mm2	Power wire dia. mm	Power cond. dia. mm	Screen wire dia. mm	Pilot size mm2	Pilot wire dia. mm	Pilot cond. dia. mm	Max tension kN	Overall dia. mm	Weight kg/km
25	0.41	6.8	0.31	10	0.41	4.2	1.1	60.6	550
35	0.41	8.5	0.31	10	0.41	4.2	1.6	64.9	640
50	0.41	10.3	0.31	10	0.41	4.2	2.3	68.5	720
70	0.51	11.9	0.31	16	0.41	4.2	3.2	72.4	830
95	0.51	13.5	0.31	16	0.41	4.2	4.3	77.1	960
120	0.51	15.5	0.31	16	0.41	4.2	5.4	81.4	1100
150	0.51	17.3	0.31	25	0.41	6.8	6.8	85.6	1260

TYPE 622-ECC DIMENSIONS			
Conductor size mm2	ECC size mm2	ECC max. wire dia. mm	Nominal weight kg/km
25	16	0.41	550
35	25	0.41	640
50	25	0.41	730
70	35	0.41	840
95	50	0.41	980
120	70	0.51	1130
150	95	0.51	1300

NOTES

Nominal dimensions and weights are provided for cable selection. Actual cable dimensions may vary due to manufacturing tolerances.

TECHNICAL DATA

Complete nominal dimensional data. Source ordering codes have been omitted.

ELECTRICAL CHARACTERISTICS									
Cond. size mm2	DC res. 20 deg C oh/km	DC res. 90 deg C oh/km	React. oh/km	Min screen res. oh/km	Min ECC res. oh/km	Current 30 deg C A	Cond. S/C kA 1s	Screen S/C kA 1s	ECC S/C kA 1s
25	0.795	1.05	0.145	1.6	0.7	105	3.1	1.6	3.6
35	0.565	0.749	0.135	1.2	0.5	130	4.3	2.1	5.0
50	0.393	0.521	0.127	0.8	0.5	160	6.1	3.1	5.0
70	0.277	0.368	0.122	0.7	0.4	195	8.5	3.5	7.5
95	0.210	0.279	0.117	0.6	0.3	230	11.6	4.1	9.0
120	0.164	0.218	0.111	0.6	0.23	260	14.6	4.1	11.5
150	0.132	0.176	0.106	0.6	0.18	300	18.3	4.1	14.0

SERVICE CONDITIONS	
Parameter	Value
Voltage rating	12.7/22 kV
Ambient rating basis	Current rating at 30 deg C ambient
Short circuit rating	Values shown are kA for 1 second

CERTIFICATIONS

